

Quick Start Guide

MTR-EVUE-10.4



Includes rugged metal enclosure, on screen display, and standard VESA compliant 75mm mounting holes.

Features:

640x480

4096 Colors

0.33 x .033 mm pixel pitch

VGA input

Resistive Touch Screen Versions Available

NTSC Option Available

5 Volt Operation

Contents of the MTR-EVUE-10.4 :

1	MTR-EVUE-10.4	
1	VGA Input Cable	CBL-VGA-6'
1	INSTRUCTION SHEET	Rev. 1.0

Quick Installation Procedure

1. Configure your computer display resolution to 640 x 480. Set refresh rate between **60-70 Hz (very important)**.
2. To change the video settings in the windows environment go to "Control Panel", select display icon. Click on "Setting's" to adjust display resolution, then click "Advanced" to change refresh rate. Power down the computer.
3. Connect the VGA cable (15 pin HD D-Sub connector) to the Video output connector on back of the computer.
4. Apply a 12 - 18 volt @ 1.5A minimum power source to the 2.5mm power jack. (tip is +)
5. Apply power to computer and to the LCD display.
6. Use the push buttons (if needed for centering) located on the lower back of LCD module to adjust the positioning and the quality of the image. Select menu with push button to change . The settings are saved permanently.